



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	VO	RS	R/W	E	D0	D1	D2	D3	D4	D5	D6	D7	K(-)	A(+)

NOTES:

- DISPLAY TYPE: STN/YELLOW -GREEN
- VIEWING DIRECTION: 6:00
- POLARIZER MODE: TRANFLECTIVE/POSITIVE
- OPERATING TEMP:  $0^{\circ}\text{C} \text{--} +60^{\circ}\text{C}$
- STORAGE TEMP:  $-20^{\circ}\text{C} \text{--} +70^{\circ}\text{C}$
- LCD OPERATING VOLTAGE: 18.5V
- DRIVE METHOD: 1/64DUTY 1/9BIAS
- CONTROLLER: KS0108X2
- BACKLIGHT: LED(YELLOW -GREEN;4.2DCV)
- ALL UNMARKED TOLERANCES:  $\pm 0.3\text{mm}$
- BEZEL(THICKNESS:0.6mm) IS TO BE PAINTED BLACK

北京中显电子有限公司, <a href="http://www.zxlcd.com">www.zxlcd.com</a>				
绘图:	型号:	ZX2004A	单位:	mm
审核:	版本号:	08V01	电话:	52926620
批准:	日期:		传真:	52926621